

CHOOSING THE RIGHT SENSAPHONE SYSTEM

FOR MONITORING LIVESTOCK



Sentinel

Sentinel Cellular

Sentry

Inputs	12	12	5
Outputs	1	1	1
Input Type			
Dry Contact	✓	✓	✓
Thermistor	-109° to 168 °F -85° to 76 °C	-109° to 168 °F -85° to 76 °C	-109° to 115°F -85° to 57°C
4-20mA	✓	✓	
Remote Programming	✓	✓	✓
Alarm Notifications	Unlimited	Unlimited	Unlimited
Alarm Delivery			
Offline Status Alarm	✓	✓	✓
Voice Phone Call	Optional	✓	✓
Email	✓	✓	✓
SMS Text Message	Optional	✓	✓
Audit Trails	✓	✓	✓
Reporting	✓	✓	
Mobile App	✓	✓	✓
Web Status	✓	✓	✓
Datalogging	✓	✓	
Communication	Ethernet	4G Cellular	4G Cellular
Enclosure	Metal or NEMA-4X	NEMA-4X	Metal or NEMA-4X
Mounting	Table or wall	Wall	Table or wall
Battery Backup	8 Hours	8 Hours	12 Hours
Monthly Fee	Optional/\$6.95	\$24.95	\$14.95

SENSAPHONE®
REMOTE MONITORING SOLUTIONS

901 Tryens Road, Aston, PA 19014 | 877-373-2700 | www.sensaphone.com